


# 583499

## Mobile dust extractor

### CTL 26 E GB 240V



#### Performance features



#### Strengths and benefits

- Approved for dust category L
- Antistatic function prevents static developing during work
- Constantly high suction because of the compact high performance turbine
- Attachment of Systainers via Sys-Dock
- Hose garage and cable windup for greater tidiness and safety
- Economical because of the optimal use of the available volume with a SELFCLEAN filter bag in the container

#### Main applications

- For dust with limit values > 1 mg/m<sup>3</sup>
- Flexible and clean in the workshop and at the construction site thanks to a compact design and a container volume of 26 litres
- Integral automatic electronic switch-on/shut-off for extraction from electric power tools
- Suitable for both wet and dry extraction

#### Items Included

- SELFCLEAN filter bag
- suction hose Ø 27 mm x 3,5 m-AS
- hose holder
- Sys dock
- cable holder

#### Packaging

in a carton

#### Technical data

Power consumption	350-1200	W
Airflow max.	3900	l/min
Max. vacuum	24000	Pa
Filter surface area	6318	cm <sup>2</sup>
Rubber-insulated mains cable	7,5	m
Container/Filter bag capacity	26/24	l
Dimensions (L x W x H)	630 x 365 x 540	mm
Max. appliance socket connected load	2400	W
weight	13,9	kg